



877-79W-TOOL www.weddletoolco.com

WTC 4-Point Fan Hanger Installation – Super-Vac Bar

- Place the 4-Point Fan Hanger Assembly over the body of the Super-Vac Bar aligning the Cut-Out on the Hanger Assembly opposite (180 Degrees) from the Handle on the Super-Vac Bar.
- Secure the Velcro closures on the bottom of the Hanger Assembly.
- Secure the (3) Velcro Safety Loops around the body of the Super-Vac Bar.
- With the 4-Point Fan Hanger attached, the Super-Vac Bar should always be installed with the Operation Handle “Towards” the Exhaust Fan.
- The 4-Point Hanger Assembly Adjustment Straps should always hang over the “TOP” of the Super-Vac Bar.



Fan Hanger Hardware Kit Installation

- 1 Fan Hanger Hardware Kit is included with each 4-Point Fan Hanger.
- Secure the attachment hardware to the top of the ventilation fan as follows:
 - Hardware should be attached to the top outside corners of the fan.
 - Hold the hardware in place on the fan and mark each hole.
 - Drill a 3/16” hole at the four marked placements on the fan.
 - Secure the attachment D Ring with the provided 3/16” pan head bolt and 3/16” nylon lock nut.
 - D Rings should be attached flush with the top of the fan when in the folded down position.

